

Barcode-reader

SUNMI 2D Handheld Scanner

- Equipped with a high-performance imaging chip, that captures even the shakiest frames, this scanner has a high motion tolerance that doesn't compromise on quality.
 - The ultra-quick decoding algorithm is the true definition of speed as it accurately identifies folded, colored and even distorted bar codes for easy accessibility.
 - The scanner briefly vibrates to let you know when a scan is complete so you never miss a code.
 - With looks that follow the latest design trends, the scanner enhances your store's image.
 - Comes with a three-year warranty(which even covers the built-in wire rods)
- *Does not cover physical damage



Scanning Barcode



Mobile Payment



















Drop-Proof



Plug and Play

SUNMI 2D Handheld Scanner

Technical specifications

 OS Windows/IOS Android/Linux	 Image sensor CMOS	 Pixel 640*480	 Reading precision ≥3mil	 Reading depth of field EAN13 (13mil) 55mm-300mm QR CODE (15mil) 35mm-190mm
 Lighting White LED	 External dimension 160*95*71mm	 Prompt method Buzzer, vibrator, LED prompt	 Focusing Red light LED 625nm	 Communication interface USB 2.0 TypeA male connector
 Field of view angle Horizontal 45° Vertical 34°	 Adapter Operating voltage: DC5V±5% Operating current: <500mA	 Symbol contrast ≥30%	 Environment Operating temperature: -10℃~50℃ Storage temperature: -40℃~70℃ Relative humidity: 5%~95% (no condensation) Electrostatic protection: ±8kV (direct discharge) ±15kV (air discharge) Drop height:1.2 meters	 Barcode sensitivity Inclined ±50° / Rotary 360° / Deflected ±50°
 Symbologies 1D: Code128, UCC/EAN-128, AIM128, EAN-8, EAN-13, ISBN/ISSN, UPC-E, UPC-A, Interleaved 2 of 5, ITF-6, ITF-4, Matrix 2 of 5, Industrial 25, Standard 25, Code39, Codabar, Code 93, Code 11, Plessey, MSI-Plessey, RSS-14, RSS-Limited, RSS-Expand 2D: PDF417, QR Code, Data Matrix				

Note:
1. The actual scan depth and angle depends on the operating environment and the size of the barcode, making it necessary to adjust the relative positioning of the device and the document or device containing the barcode to ensure a correct reading
2. Actual product specifications when sold take precedence over what may be listed at this catalogue; Any changes may be made without prior notification